



## Physical Features

- Protective architectural dark bronze power coating to ensure long lasting performance even in harsh environment
- Compact and light weighted, ideal for confined spaces
- Wet location rated for outdoor application
- IES type III for optimized light distribution
- Optional installation of Arm Mount and Wall Mount



## Application

Parks, shopping malls, outlets, plazas, city halls, historical sites; parking lots; road lighting.

## Electronic Features

- Light output from 13400 lumen up to 38000 lumen
- High lighting efficiency of around 130 lm/W and long life span of 50,000 hours
- 105W-300W Replaces 250W-1000W MH
- CRI ≥ 70
- 0-10V dimming optional

## Other information

- cUL listed and DLC listed
- 5-year limited warranty for DLC approved

## Installation













SSF - Square Slipfitter



AM - Arm Mount (Square or Round poles)



WM - Wall Mount









Order Code	Model Number	Description	DLC	Watts	Volts (V)	Hours Rating	Optics/ Distribution	Init. Lm	CCT(K)	CRI	Wet Loc	Dimensions LxWxH (mm)
3667106	SSL-SB1/105W/50/UNV/DB/SSF/D	SSL 105W Shoebox I, 50K, 120-277V, Dark Bronze, Dimmable, Square Slipfitter		105	120-277	50,000	Type III	13400	5000K	70	Y	12.4X11.26X3.07
3667207	SSL-SB1/110W/50/HVU/DB/SSF/D	SSL 110W Shoebox I, 50K, 347-480V, Dark Bronze, Dimmable, Square Slipfitter		105	347-480	50,000	Type III	13400	5000K	70	Y	12.4X11.26X3.07
3667107	SSL-SB1/150W/50/UNV/DB/SSF/D	SSL 150W Shoebox I, 50K, 120-277V, Dark Bronze, Dimmable, Square Slipfitter		150	120-277	50,000	Type III	20000	5000K	70	Y	12.4X14.6X3.07
3667208	SSL-SB1/150W/50/HVU/DB/SSF/D	SSL 150W Shoebox I, 50K, 347-480V, Dark Bronze, Dimmable, Square Slipfitter		150	347-480	50,000	Type III	20000	5000K	70	Y	12.4X14.6X3.07
3667108	SSL-SB1/200W/50/UNV/DB/SSF/D	SSL 200W Shoebox I, 50K, 120-277V, Dark Bronze, Dimmable, Square Slipfitter		200	120-277	50,000	Type III	24500	5000K	70	Y	12.4X14.6X3.07
3667209	SSL-SB1/200W/50/HVU/DB/SSF/D	SSL 200W Shoebox I, 50K, 347-480V, Dark Bronze, Dimmable, Square Slipfitter		200	347-480	50,000	Type III	24500	5000K	70	Y	12.4X14.6X3.07
3668100	SSL-SB1/250W/50/UNV/DB/SSF/D	SSL 250W Shoebox I, 50K, 120-277V, Dark Bronze, Dimmable, Square Slipfitter		250	120-277	50,000	Type III	33000	5000K	70	Y	12.4X22.89X3.54
3668202	SSL-SB1/250W/50/HVU/DB/SSF/D	SSL 250W Shoebox I, 50K, 347-480V, Dark Bronze, Dimmable, Square Slipfitter		250	347-480	50,000	Type III	33000	5000K	70	Y	12.4X22.89X3.54
3668101	SSL-SB1/300W/50/UNV/DB/SSF/D	SSL 300W Shoebox I, 50K, 120-277V, Dark Bronze, Dimmable, Square Slipfitter		300	120-277	50,000	Type III	38000	5000K	70	Y	12.4X22.89X3.54
3668203	SSL-SB1/300W/50/HVU/DB/SSF/D	SSL 300W Shoebox I, 50K, 347-480V, Dark Bronze, Dimmable, Square Slipfitter		300	347-480	50,000	Type III	38000	5000K	70	Y	12.4X22.89X3.54
<b>Photocell Sensor</b>												
366006	SSL-FL/SB/UNV/PC	Flood/ShoeBox Photocell 120-277V										

Ambient Operating Temperature -40°C ~ +45°C

For the latest stock status please refer to your price list or send us an email at [sales@turolight.com](mailto:sales@turolight.com)

## How our Model No. Works:

### Ordering Information

							
SSL	SB1	105W	50	UNV	DB	KNC	D
Family	Fixture Style	Wattage	CCT (K)	Voltage	Body Finish	Bracket Type	Dimming
	SB1 - Show Box	105W 110W 150W 200W 250W 300W	40 - 4000K 50 - 5000K	UNV - 120-277V HVU - 347-480V	DB - Dark Bronze	SSF - Square Slipfitter WM - Wall Mounting AM - Arm Mount (Square or Round poles)	D - 0~10V Dimming

Distributed by: