



### Key Features

- 450-1600 Lumens
- Energy Star Listed
- Omni-Directional 330° beam
- Dimmable
- Replaces 40-100W incandescent
- High CRI (80+)
- 25,000 hour average life
- Suitable for damp locations
- Reduces energy consumption up to 80%
- No UV, no infrared and mercury free



### Applications

- Hospitality
- Retail

- Art galleries and museums
- Shopping Malls
- Offices
- Restaurants
- Residential

### General Usage

- Table/Floor lamps
- Wall Sconces
- Pendants

### Other information

- Operating temperature range between -20°C and +45°C
- UL/cUL listed, FCC compliant, RoHS compliant
- 3-year limited warranty in commercial and residential use (2-year limited warranty for VIV-A19/17/\*\*\*\*\*)

Order Code	Model Number	ES	Watts	Base	Volts	Hour Rating	Beam Angle	Initial Lumens	CCT (K)	CRI	Incandescent Replacement	EFA*	Damp Location	M.O.L. (inch)	Case Qty.
1762733	VIV-A21/14.5W/30/D		14.5	E26	120	25,000	330°	1600	3000	80	100W	Y	Y	4.7	40
1762815	VIV-A21/14.5W/40/D		14.5	E26	120	25,000	330°	1600	4000	80	100W	Y	Y	4.7	40
1762824	VIV-A19/11W/40/D		11	E26	120	25,000	330°	1100	4000	80	75W	Y	Y	4.5	40
1762179	VIV-A19/X8/8.5W/27/D		8.5	E26	120	25,000	280°	800	2700	80	60W	-	Y	4.2	40
1762725	VIV-A19/X8/8.5W/30/D		8.5	E26	120	25,000	280°	800	3000	80	60W	-	Y	4.2	40
1762811	VIV-A19/X8/8.5W/40/D		8.5	E26	120	25,000	280°	800	4000	80	60W	-	Y	4.2	40
1762265	VIV-A19/17/9W/30/D		9	E26	120	15,000	250°	800	3000	80	60W	Y	Y	4.3	40
1762180	VIV-A19/X8/6W/27/D		6	E26	120	25,000	280°	450	2700	80	40W	-	Y	4.2	40
1762726	VIV-A19/X8/6W/30/D		6	E26	120	25,000	280°	450	3000	80	40W	-	Y	4.2	40
1762126	VIV-A19/6W/27/D	-	6	E26	120	25,000	330°	450	2700	80	40W	Y	Y	4.2	40
1762455	VIV-A19/6W/40/D	-	6	E26	120	25,000	330°	450	4000	80	40W	Y	Y	4.2	40
1762834	VIV-A19/17/6W/40/D		6	E26	120	15,000	250°	450	4000	80	40W	Y	Y	4.3	40

\*Enclosed Fixture Application.

For the latest stock status please refer to your price list or send us an email at [sales@turolight.com](mailto:sales@turolight.com)

How to read: VIV - A19/X8 / 8.5W / 27 / D