



Key Features

- Par38 21.5W/1750lm
- Energy Star Listed
- Suitable for enclosed fixture
- Suitable for wet/damp and outdoor/indoor location*
- Optional Silver Housing is available
- Dimmable
- High CRI (83+)
- 25,000 hour average life
- Even light distribution
- Reduces energy consumption up to 80%
- No UV, no infrared and mercury free

*See data on next page for applicable models



Other information

- Operating temperature range between -20°C and +40°C
- UL/cUL listed, FCC compliant, RoHS compliant
- 3-year limited warranty in commercial and residential use*

Replacement Equivalent

Par38: 21.5W replaces 120W halogen, 16.5W replace 100W halogen
 Par30: 12W replaces 75W halogen, 10W replaces 75W halogen
 Par20: 6.5W replaces 50W halogen

*See www.turolight.com for specific details





Applications




















- Hospitality
- Retail
- Art galleries and museums
- Shopping Malls
- Offices
- Restaurants
- Residential

General Usage

- Recessed Down Lights/Pot Lights
- Track Lights
- Specialty

Dimensions



| Order Code | Model Number | ES | Watts | Base | Volts | Hour Life | Beam Angle | Init. Lum. | CCT (K) | CBCP | CRI | Wet Loc. | Damp Loc. | MOL (inch) | CS Qty. |
|--------------|----------------------------|---|-------|------|-------|-----------|------------|------------|---------|------|-----|----------|-----------|------------|---------|
| PAR38 | | | | | | | | | | | | | | | |
| 1764205 | VIV-PAR38/21.5W/30/FL25/D |  | 21.5 | E26 | 120 | 25,000 | 25° | 1750 | 3000 | 6768 | 83 | Y | - | 5.04 | 10 |
| 1764405 | VIV-PAR38/21.5W/40/FL25/D |  | 21.5 | E26 | 120 | 25,000 | 25° | 1750 | 4000 | 7908 | 83 | Y | - | 5.04 | 10 |
| 1764206 | VIV-PAR38/21.5W/30/WFL40/D |  | 21.5 | E26 | 120 | 25,000 | 40° | 1750 | 3000 | 2627 | 83 | Y | - | 5.04 | 10 |
| 1764406 | VIV-PAR38/21.5W/40/WFL40/D |  | 21.5 | E26 | 120 | 25,000 | 40° | 1750 | 4000 | 2760 | 83 | Y | - | 5.04 | 10 |
| 1763229 | VIV-PAR38/16.5W/30/FL25/D |  | 16.5 | E26 | 120 | 25,000 | 25° | 1160 | 3000 | 4904 | 83 | Y | - | 5.04 | 10 |
| 1763430 | VIV-PAR38/16.5W/40/FL25/D |  | 16.5 | E26 | 120 | 25,000 | 25° | 1160 | 4000 | 4904 | 83 | Y | - | 5.04 | 10 |
| 1763230 | VIV-PAR38/16.5W/30/WFL40/D |  | 16.5 | E26 | 120 | 25,000 | 40° | 1160 | 3000 | 2526 | 83 | Y | - | 5.04 | 10 |
| 1763431 | VIV-PAR38/16.5W/40/WFL40/D |  | 16.5 | E26 | 120 | 25,000 | 40° | 1160 | 4000 | 2526 | 83 | Y | - | 5.04 | 10 |
| PAR30 | | | | | | | | | | | | | | | |
| 1762739 | VIV-PAR30LN/12W/30/FL25/D |  | 12 | E26 | 120 | 25,000 | 25° | 850 | 3000 | 3761 | 83 | - | Y | 4.57 | 20 |
| 1762826 | VIV-PAR30LN/12W/40/FL25/D |  | 12 | E26 | 120 | 25,000 | 25° | 850 | 4000 | 3761 | 83 | - | Y | 4.57 | 20 |
| 1762740 | VIV-PAR30LN/12W/30/WFL40/D |  | 12 | E26 | 120 | 25,000 | 40° | 850 | 3000 | 1647 | 83 | - | Y | 4.57 | 20 |
| 1762827 | VIV-PAR30LN/12W/40/WFL40/D |  | 12 | E26 | 120 | 25,000 | 40° | 850 | 4000 | 1437 | 83 | - | Y | 4.57 | 20 |
| 1762741 | VIV-PAR30/10W/30/FL25/D |  | 10 | E26 | 120 | 25,000 | 25° | 750 | 3000 | 3042 | 83 | - | Y | 3.46 | 20 |
| 1762828 | VIV-PAR30/10W/40/FL25/D |  | 10 | E26 | 120 | 25,000 | 25° | 750 | 4000 | 3042 | 83 | - | Y | 3.46 | 20 |
| 1762742 | VIV-PAR30/10W/30/WFL40/D |  | 10 | E26 | 120 | 25,000 | 40° | 750 | 3000 | 1353 | 83 | - | Y | 3.46 | 20 |
| 1762829 | VIV-PAR30/10W/40/WFL40/D |  | 10 | E26 | 120 | 25,000 | 40° | 750 | 4000 | 1349 | 83 | - | Y | 3.46 | 20 |
| PAR20 | | | | | | | | | | | | | | | |
| 1762743 | VIV-PAR20/6.5W/30/FL25/D |  | 6.5 | E26 | 120 | 25,000 | 25° | 460 | 3000 | 1459 | 83 | - | Y | 3.19 | 40 |
| 1762830 | VIV-PAR20/6.5W/40/FL25/D |  | 6.5 | E26 | 120 | 25,000 | 25° | 460 | 4000 | 1459 | 83 | - | Y | 3.19 | 40 |
| 1762744 | VIV-PAR20/6.5W/30/WFL40/D |  | 6.5 | E26 | 120 | 25,000 | 40° | 460 | 3000 | 703 | 83 | - | Y | 3.19 | 40 |
| 1762831 | VIV-PAR20/6.5W/40/WFL40/D |  | 6.5 | E26 | 120 | 25,000 | 40° | 460 | 4000 | 780 | 83 | - | Y | 3.19 | 40 |

For the latest stock status please refer to your price list or send us an email at sales@turolight.com

How to read our model number

VIV / PAR38 / 21.5W / 30 / FL25 / D
 LED Class Reflector Type Wattage CCT(K) Beam Angle Dimmable

Distributed by: